



GM015 - 1-1/2" Oval Gear Pulse Meter



The GM015 is our medium to large capacity meter with 1-1/2-inch fittings. Optional 150 lb. ANSI Flanges and Tri-Clover® Fittings are available on the GM015. The GM015 can be installed without regard to straight pipe runs making installation easy.

Select Your Body Material:

- Aluminum
- Bronze
- Stainless Steel



Features and Benefits:

- ✓ Extremely accurate even with viscous fluids.
- ✓ Handles particles sizes to 0.011"/0.28 mm.
- ✓ Meter design minimizes the number of wear-able parts – extending product life.
- ✓ Comes with Read Switch as standard, Hall Effect Sensor optional.
- ✓ Choose from a variety of Output and Display Options.
- ✓ Certificate of Accuracy supplied with meter.

GM015 - SPECIFICATIONS

Fitting Type:	
Aluminum:	BSP or NPT (Female), 150 lb. ANSI Flange
Bronze:	BSP or NPT (Female)
Stainless Steel:	BSP or NPT (Female), 150 lb. ANSI Flange or Tri-Clover® Fittings
Sensor Options:	Reed Switch / Hall Effect Sensor
Rotor Materials:	PPS or High Viscosity PPS, 316 Stainless Steel or High Viscosity Stainless Steel
O-Ring:	Viton (Standard), Teflon® (Optional)
Output Options:	Pulse Out or Local 4-20 mA Transmitter
Display Options:	Standard LC Display or Local 4-20 mA with Standard Display
Flow Range:	2.6 - 66 GPM (10 - 250 LPM)
Flow Range @ < 5 cps:	4.0 - 62.5 GPM (15 - 235 LPM)
Accuracy:	± 0.5% of reading
Repeatability:	± 0.03%
Maximum Viscosity:	Standard Rotors: 1,000 cps High Viscosity Rotors: 1,000,000 cps
Pressure Rating:	
Aluminum:	800 PSI / 55 BAR or Flange Rule
Bronze:	800 PSI / 55 BAR
Stainless Steel:	800 PSI / 55 BAR or Flange Rule
Maximum Temperature:	
PPS Rotors:	176°F / 80°C
SS Rotors:	248°F / 120°C
Typical K-Factor:	
Single Pickup:	54.9 PPG / 14.5 PPL
Double Pickup:	109.8 PPG / 29 PPL
Wetted Mat'l. - Housing:	
Aluminum:	Aluminum
Bronze:	Bronze
Stainless Steel:	316 Stainless Steel
Wetted Mat'l. - Bearings:	PPS / Carbon
Wetted Mat'l. - Shaft:	316 Stainless Steel
Frequency Range:	2.4 - 60.4 Hz @ 2.6 - 66 GPM
Strainer Size:	60 mesh
Shipping Weight (approx.):	
Aluminum:	10.0 lbs. (4.5 kg) - Pulse 12.0 lbs. (5.4 kg) - 150 lb. ANSI Flange
Bronze:	18.7 lbs. (8.49 kg) - Pulse
Stainless Steel:	18.4 lbs. (8.4 kg) - Pulse 20.9 lbs. (9.4 kg) - 150 lb. ANSI Flange 19.2 lbs. (8.7 kg) - Tri-Clover® Fittings
Remote Display:	Option Available: Model GG500-40
Remote Transmitter:	Options Available: Model GA500 & GX500-40

BUY SMART . BUY VALUE . BUY